NISTIR 8104-11

NIST Time and Frequency Bulletin

Karen Hansen Lichtfuss, Editor

This publication is available free of charge from: https://doi.org/10.6028/NIST.IR.8104-11



NISTIR 8104-11

NIST Time and Frequency Bulletin

Karen Hansen Lichtfuss, Editor Time and Frequency Division Physical Measurement Laboratory

This publication is available free of charge from: https://doi.org/10.6028/NIST.IR.8104-11

November 2016



U.S. Department of Commerce Penny Pritzker, Secretary

National Institute of Standards and Technology Willie May, Under Secretary of Commerce for Standards and Technology and Director

NIST TIME AND FREQUENCY BULLETIN NIST IR 8104-11

No. 708 November 2016

1.	GENERAL BACKGROUND INFORMATION	. 2
2.	TIME SCALE INFORMATION	. 2
	BROADCAST OUTAGES OVER FIVE MINUTES AND WWVB PHASE PERTURBATIONS	. 4
4.	NOTES ON NIST TIME SCALES AND PRIMARY STANDARDS	. 4
5.	UTC (NIST) – AT1 PARAMETERS	5

This bulletin is published monthly. Address correspondence to:

Karen Hansen Lichtfuss, Editor Time and Frequency Division National Institute of Standards and Technology 325 Broadway Boulder, CO 8O3O5-3328 (3O3) 497-3295 Email: <u>karen.hansenlichtfuss@nist.gov</u>



U.S. DEPARTMENT OF COMMERCE, Penny Pritzker, Secretary NATIONAL INSTITUTE OF STANDARDS AND TECHNOLOGY, Willie May, Under Secretary of Commerce for Standards and Technology and Director

1. GENERAL BACKGROUND INFORMATION

	ACRONYMS AND ABBREVIATIONS	JSED IN THIS BU				
ACTS	- Automated Computer Time Service					
BIPM	- Bureau International des Poids et Mesures					
GPS	 Global Positioning System 					
IERS	- International Earth Rotation Service					
MC	- Master Clock					
MJD	 Modified Julian Date 					
NIST	 National Institute of Standards and Technology 	ns	 nanosecond 			
SI	 International System of Units 	μs	 microsecond 			
TA	- Atomic Time	ms	 millisecond 			
TAI	 International Atomic Time 	S	- second			
USNO	 United States Naval Observatory 	min	- minute			
UT1	- Universal Time (Astronomical)					
UTC	- Coordinated Universal Time					

2. TIME SCALE INFORMATION

The values listed below are based on data from the IERS, the USNO, and NIST. The UTC(USNO,MC) - UTC(NIST) values are averaged measurements from all available common-view GPS satellites (see bibliography on page 5). UTC - UTC(NIST) data are on page 3.

0000 HOURS COORDINATED UNIVERSAL TIME							
October 2016	MJD	UT1-UTC(NIST) (±5 ms)	UTC(USNO,MC) - UTC(NIST) (±20 ns)				
6	57667	- 284 ms	2.5 ns				
13	57674	- 293 ms	3.8 ns				
20	57681	- 306 ms	2.2 ns				
27	57688	- 316 ms	0.2 ns				

The master clock pulses used by the WWV, WWVH, and WWVB time-code transmissions are referenced to the UTC (NIST) time scale. Occasionally, 1 s is added to the UTC time scale. This second is called a leap second. Its purpose is to keep the UTC time scale within ± 0.9 s of the UT1 astronomical time scale, which changes slightly due to variations in the Earth's period of rotation.

NOTE: A positive leap second will be added at the end of December 2016.

Positive leap seconds, beginning at 23 h 59 min 60 s UTC and ending at 0 h 0 min 0 s UTC, were inserted in the UTC time scale on 30 June 1972, 1981-1983, 1985, 1992-1994, 1997, 2012, 2015 and on 31 December 1972-1979, 1987, 1989, 1990,1995, 1998, 2005, 2008.

The use of leap seconds ensures that UT1 - UTC will always be held within ± 0.9 s. The current value of UT1 - UTC is called the DUT1 correction. DUT1 corrections are broadcast by WWV, WWVH, WWVB, and ACTS and are printed below. These corrections may be added to the received UTC time signals in order to obtain UT1.

The difference between UTC(NIST) and UTC has been within ± 100 ns since July 6, 1994. The table below shows values of UTC - UTC(NIST) as supplied by the BIPM in their *Circular T* publication for the most recent 310-day period in which data are available. Data are given at ten-day intervals. Five-day interval data are available in *Circular T*.

0000 Hours Coordinated Universal Time						
DATE	MJD	UTC-UTC(NIST), ns				
Oct. 28, 2016	57689	1.8				
Oct. 18, 2016	57679	4.5				
Oct. 8, 2016	57669	5.5				
Sep. 28, 2016	57659	4.1				
Sep. 18, 2016	57649	1.3				
Sep. 8,2016	57639	0.4				
Aug. 29, 2016	57629	-1.6				
Aug. 19, 2016	57619	-4.7				
Aug. 9, 2016	57609	-4.2				
Jul. 30, 2016	57599	-4.1				
Jul. 20, 2016	57589	-2.0				
Jul. 10, 2016	57579	-0.3				
Jun. 30, 2016	57569	0.7				
Jun. 20, 2016	57559	1.1				
Jun. 10, 2016	57549	0.9				
May 31, 2016	57539	0.4				
May 21, 2016	57529	-0.3				
May 11, 2016	57519	-0.6				
May 1, 2016	57509	-2.0				
Apr. 21, 2016	57499	-1.4				
Apr. 11, 2016	57489	3.4				
Apr. 1, 2016	57479	4.4				
Mar. 22, 2016	57469	2.8				
Mar. 12, 2016	57459	0.9				
Mar. 2, 2016	57449	-0.4				
Feb. 11, 2016	57439	-4.9				
Feb. 11, 2016	57429	-7.6				
Feb. 01, 2016	57419	-8.6				
Jan. 22, 2016	57409	-7.4				
Jan. 12, 2016	57399	-3.0				
Jan. 02, 2016	57389	1.7				
Dec. 23, 2015	57379	3.5				
Dec. 13, 2015	57369	4.3				
Dec. 03, 2015	57359	6.4				

3. BROADCAST OUTAGES OVER FIVE MINUTES AND WWVB PHASE PERTURBATIONS

OUTAGES OF 5 MINUTES OR MORE						PH	IASE PER 2 I	FURBATIC ms	INS
Station	Oct 2016	MJD	Began UTC	Ended UTC	Freq.	Oct 2016	MJD	Began UTC	End UTC
WWVB	None	None	None	None	None	None			
WWV	None					None			
WWVH	None					None			

4. NOTES ON NIST TIME SCALES AND PRIMARY STANDARDS

Primary frequency standards developed and operated by NIST are used to provide accuracy (rate) input to the BIPM and to provide the best possible realization of the SI second. NIST-F1 and NIST F-2, cold-atom cesium fountain frequency standards, have served as the U.S. primary standards of time and frequency since 1999. The uncertainty of NIST-F2 is currently about 1 part in 10¹⁶.

The AT1 scale is run in real-time by use of data from an ensemble of cesium standards and hydrogen masers. It is a free-running scale whose frequency is maintained as nearly constant as possible by choosing the optimum weight for each clock that contributes to the computation.

UTC(NIST) is generated as an offset from our real-time scale AT1. It is steered in frequency towards UTC by use of data published by the BIPM in its *Circular T*. Changes in the steering frequency will be made, if necessary, at 0000 UTC on the first day of the month, and occasionally at mid-month. A change in frequency is limited to no more than ± 2 ns/day. The frequency of UTC(NIST) is kept as stable as possible at other times.

UTC is generated at the BIPM by use of a post-processed time-scale algorithm and is not available in real-time. The parameters that we use to generate UTC(NIST) in real-time are therefore based on an extrapolation of UTC from the most recent available data.

References:

Allan, D.W.; Hellwig, H.; and Glaze, D.J., "An accuracy algorithm for an atomic time scale," Metrologia, Vol.11, No.3, pp. 133-138 (1975).

Allan, D.W.; Davis, D.D.; Weiss, M.A.; Clements, A.; Guinot, B.; Granveaud, M.; Dorenwendt, K.; Fischer, B.; Hetzel, P.; Aoki, S.; Fujimoto, M.; Charron, L.; and Ashby, N., "Accuracy of international time and frequency comparisons via global positioning system satellites in common-view," IEEE Transactions on Instrumentation and Measurement, Vol. IM-34, pp.118-125 (1985).

Heavner, T.P.; Jefferts, S.R.; Donley; E.A.; Shirley, J.H. and Parker, T.E., "NIST F1; recent improvements and accuracy evaluations," Metrologia, Vol. 42, pp. 411-422 (2005).

Jefferts, S.R.; Shirley, J.; Parker, T.E.; Heavner, T.P.; Meekhof, D.M.; Nelson, C., Levi, F.; Costanza, G.; De Marchi, A.; Drullinger, R.; Hollberg, L.; Lee, W.D.; and Walls, F.L., "Accuracy evaluation of NIST-F1," Metrologia, Vol. 39, pp. 321-336 (2002).

Lewandowski, W. and Thomas, C., "GPS Time transfer," Proceedings of the IEEE, Vol. 79, pp. 991-1000 (1991).

Parker, T.E.; Jefferts, S.R.; Heavner, T.P.; and Donley, E.A., "Operation of the NIST-F1 caesium fountain primary frequency standard with a maser ensemble, including the impact of frequency transfer noise," Metrologia, Vol. 42, pp. 423-430 (2005).

Weiss, M.A.; Allan, D.W., "An NBS Calibration Procedure for Providing Time and Frequency at a Remote Site by Weighting and Smoothing of GPS Common View Data," IEEE Transactions on Instrumentation and Measurement, Vol. IM-36, pp. 572-578 (1987).

5. UTC(NIST) - AT1 PARAMETERS

The table below lists parameters that are used to define UTC(NIST) with respect to our real-time scale AT1. To find the value of UTC(NIST) - AT1 at any time T (expressed as a Modified Julian Date, including a fraction if needed), the appropriate equation to use is the one for which the desired T is greater than or equal to the entry in the T₀ column and less than the entry in the last column. The values of x_{ls} , x, and y for that month are then used in the equation below to find the desired value. The parameters x and y represent the offsets in time and frequency, respectively, between UTC(NIST) and AT1; the parameter x_{ls} is the number of leap seconds applied to both UTC(NIST) and UTC, as specified

$UTC(NIST) - AT1 = x_{is} + x + y^{*}(T - T_{0})$						
Month	xls (s)	x (ns)	y (ns/d)	T0 (MJD)	Valid until 0000 on: (MJD)	
Dec 16	-36	-438733.45	-37.00*	57723	57754	
Nov 16	-36	-437694.75	-37.00	57704	57723*	
Nov 16	-36	-437694.75	-37.30	57695	57704†	
Nov 16	-36	-437620.95	-36.90	57693	57695†	
Oct 16	-36	-436956.75	-36.90	57675	57693	
Oct 16	-36	-436510.35	-37.20	57663	57675†	
Oct 16	-36	-436472.9	-37.50	57662	57663†	
Sep 16	-36	-435910.4	-37.50	57647	57662	
Sep 16	-36	-435350.9	-37.30	57632	57647†	
Aug 16	-36	-434936.7	-37.65	57621	57632	
Aug 16	-36	-434191.7	-37.25	57601	57621†	
Jul 16	-36	-434079.95	-37.25	57598	57601	
Jul 16	-36	-433041.2	-37.10	57570	57598†	
Jun 16	-36	-431923.7	-37.25	57540	57570	
May 16	-36	-431476.7	-37.25	57528	57540	
May 16	-36	-430771.8	-37.1	57509	57528†	
Apr 16	-36	-430697.6	-37.1	57507	57509	
Apr 16	-36	-429931.05	-36.5	57486	57507†	
Apr 16	-36	-429672.75	-36.9	57479	57486†	
Mar 16	-36	-428636.75	-37.0	57451	57479	
Mar 16	-36	-428521.05	-37.3	57448	57451†	
Feb 16	-36	-427816.15	-37.3	57429	57448	
Feb 16	-36	-427556.45	-37.1	57422	57429†	
Feb 16	-36	-427446.05	-36.8	57419	57422†	
Jan 16	-36	-427014.25	-36.8	57408	57419	
Jan 16	-36	-426313.25	-36.4	57388	57408†	
Dec 15	-36	-426056.65	-36.7	57381	57388	
Dec 15	-36	-425761.45	-36.9	57373	57381†	
Dec 15	-36	-425285.65	-36.6	57360	57373†	
Dec 15	-36	-425162.45	-36.9	57357	57360†	

by the IERS. Leap seconds are not applied to AT1.

† Rate change in mid-month

*Provisional value