

Network Working Group
Internet-Draft
Intended status: Standards Track
Expires: 26 March 2024

K. Zhang
Z. Hu
J. Dong
Huawei
23 September 2023

BGP SR Policy Extensions for template
draft-zhang-idr-sr-policy-template-03

Abstract

Segment Routing(SR) Policies can be advertised using BGP. An SR Policy may has lots of attributes, and as the application and features evolve, the SR Policy may need have more and more attribute attributes. To avoid modifying BGP when attributes are added to an SR Policy, we can define a template. The identifier and content of the template are defined by the receiver of the SR Policy. The advertiser of an SR policy only needs to know the ID of the template. When advertising SR policy, the advertiser carries the template ID in the tunnel encapsulation information of the SR policy. After receiving the SR Policy information, the receiver obtains the corresponding template and content according to the template ID, thereby obtaining abundant constraint configuration information.

Requirements Language

The key words "MUST", "MUST NOT", "REQUIRED", "SHALL", "SHALL NOT", "SHOULD", "SHOULD NOT", "RECOMMENDED", "MAY", and "OPTIONAL" in this document are to be interpreted as described in BCP 14 [RFC2119] [RFC8174] when, and only when, they appear in all capitals, as shown here.

Status of This Memo

This Internet-Draft is submitted in full conformance with the provisions of BCP 78 and BCP 79.

Internet-Drafts are working documents of the Internet Engineering Task Force (IETF). Note that other groups may also distribute working documents as Internet-Drafts. The list of current Internet-Drafts is at <https://datatracker.ietf.org/drafts/current/>.

Internet-Drafts are draft documents valid for a maximum of six months and may be updated, replaced, or obsoleted by other documents at any time. It is inappropriate to use Internet-Drafts as reference material or to cite them other than as "work in progress."

This Internet-Draft will expire on 26 March 2024.

Copyright Notice

Copyright (c) 2023 IETF Trust and the persons identified as the document authors. All rights reserved.

This document is subject to BCP 78 and the IETF Trust's Legal Provisions Relating to IETF Documents (<https://trustee.ietf.org/license-info>) in effect on the date of publication of this document. Please review these documents carefully, as they describe your rights and restrictions with respect to this document. Code Components extracted from this document must include Revised BSD License text as described in Section 4.e of the Trust Legal Provisions and are provided without warranty as described in the Revised BSD License.

Table of Contents

1. Introduction	2
2. Terminology	3
3. Template ID defination	3
4. SR Policy and Tunnel Encapsulation Attribute Update	3
4.1. Template ID sub-TLV	4
5. SR Policy Operations	5
5.1. Advertisement of SR Policies	5
5.2. Reception of an SR Policy	5
6. Acknowledgements	6
7. IANA Considerations	6
8. Security Considerations	6
9. References	6
Authors' Addresses	7

1. Introduction

[I-D.ietf-idr-segment-routing-te-policy] defines some attributes encoding of the SR Policy path. However, in actual applications, there are many other attributes of SR Policy path. These attributes are valid only on the device where the SR Policy path is installed. Such attributes may include backup protection, Bidirectional Forwarding Detection information, traffic statistics collection, or in-situ Flow Information Telemetry detection information, etc. If these attributes are directly delivered through BGP, the BGP SR Policy protocol may change frequently. This document defines a general method to carry the path attributes of SR Policies.

2. Terminology

SR Policy: An ordered list of segments.

Candidate Path: the unit for signaling of an SR Policy to a headend via protocol extensions like Path Computation Element (PCE) Communication Protocol (PCEP) [RFC8664] [I-D.ietf-pce-segment-routing-policy-cp] or BGP SR Policy [I-D.ietf-idr-segment-routing-te-policy].

SRPM: SR Policy Module.

Template: A collection of attributes sets.

Template ID: The identifier of a template.

3. Template ID definition

To support the attributes extension of SR Policies, this document defines a constraint template identifier. The constraint template ID is valid only for the recipient. The SR policy publisher only needs to carry the template ID when publishing the SR policy. The receiver of the SR Policy may create a template corresponding to the template identifier in advance before receiving the SR Policy, or may define a corresponding template after receiving the template definition of the SR Policy. The template can contain any attributes on the SR Policy path, including but not limited to backup protection, Bidirectional Forwarding Detection information, traffic statistics collection, or in-situ Flow Information Telemetry detection information, etc. After receiving the SR Policy information, the receiver matches the template information based on the template ID and adds attributes to the SR Policy based on the attributes defined in the template.

Template ID is an local identifier, just to use on the headend of the SR Policy. And it is a local configured identifier, need to be unique only on the headend device. We need no further process to coordinate the template ID between multiple routers.

4. SR Policy and Tunnel Encapsulation Attribute Update

As the template ID is defined, the tunnel attribute encapsulation of the BGP SR Policy needs to be updated.

The SR Policy Encoding structure is as follows:

SR Policy SAFI NLRI: <Distinguisher, Policy-Color, Endpoint>

Attributes:
 Tunnel Encaps Attribute (23)
 Tunnel Type: SR Policy
 Binding SID
 Preference
 Priority
 Policy Name
 Policy Candidate Path Name
 Explicit NULL Label Policy (ENLP)
 Template ID
 Segment List
 Weight
 Segment
 Segment

Where Template ID indicates the template ID for the SR Policy candidate path.

4.1. Template ID sub-TLV

A new sub-TLV called Template ID sub-TLV is defined. Template ID sub-TLV specifies the template ID of an SR policy candidate path. Each sub-TLV is encoded as shown in Figure 1.




Figure 1: Figure 1: Template ID Sub-TLV

Type: Template ID, 1 octet, TBD.

Length: 6.

Flags: 1 octet of flags.

Where:

N-Flag: This flag, when set, indicates the presence of the Template Name encoding.

RESERVED: 1 octet of reserved bits. SHOULD be set to zero on transmission and MUST be ignored on receipt.

Template ID: a 4-octet value.

Template Name: Template MAY also be assigned with a template name, such template name MUST NOT be considered as identifiers for a template. The size of the template name for the template is limited to 255 bytes.

5. SR Policy Operations

5.1. Advertisement of SR Policies

When BGP advertises an SR Policy, different candidate paths of the same SR Policy may have different template IDs or the same template ID, depending on the attributes required by the candidate paths of the SR Policy.

Reflectors just need to advertise the route of SR, no need to process it.

5.2. Reception of an SR Policy

SR Policy is only to be processed on the SR Policy headend, reflectors just need to reflect the route of SR Policy, no need to process it. To make this possible, an attribute needs to be attached to the advertisement that enables a BGP speaker to determine whether it is intended to be a headend for the advertised policy. This is done by attaching one or more Route Target Extended Communities to the advertisement [RFC4360]. This process is defined in [I-D.ietf-idr-segment-routing-te-policy]. This draft does not add any extra process in this process.

Once BGP on the receiving node has determined that the SR Policy NLRI is usable, it passes the SR Policy candidate path to the SRPM. The SRPM then determine how to use the template ID in SR Policy. The SRPM find the local configured template by template ID, and get all the attributes that is configured in the template, and then process the candidate path with these attributes. For example, if the template configure seamless bfd, then the SRPM can create sbfd sessions for each Segment List in the candidate path. If there is no template find, the SRPM should ignore the template ID and use the candidate path as there is no template ID.

6. Acknowledgements

TBD.

7. IANA Considerations

This document requests that IANA allocates a new sub-TLV type as defined in Section 4.1 from the "Sub-TLVs for SR Policy" registry as specified.

Value	Description	Reference
TBD	SR Policy Template ID	This document

Figure 2: Figure 2: Template ID sub-TLV

8. Security Considerations

These extensions to BGP SR Policy do not add any new security issues to the existing protocol.

9. References

[I-D.ietf-idr-segment-routing-te-policy]
 Previdi, S., Filsfils, C., Talaulikar, K., Mattes, P., and
 D. Jain, "Advertising Segment Routing Policies in BGP",
 Work in Progress, Internet-Draft, draft-ietf-idr-segment-
 routing-te-policy-23, 25 July 2023,
<https://datatracker.ietf.org/doc/html/draft-ietf-idr-segment-routing-te-policy-23>.

- [I-D.ietf-pce-segment-routing-policy-cp]
Koldychev, M., Sivabalan, S., Barth, C., Peng, S., and H. Bidgoli, "PCEP extension to support Segment Routing Policy Candidate Paths", Work in Progress, Internet-Draft, draft-ietf-pce-segment-routing-policy-cp-12, 24 July 2023, <<https://datatracker.ietf.org/doc/html/draft-ietf-pce-segment-routing-policy-cp-12>>.
- [RFC2119] Bradner, S., "Key words for use in RFCs to Indicate Requirement Levels", BCP 14, RFC 2119, DOI 10.17487/RFC2119, March 1997, <<https://www.rfc-editor.org/info/rfc2119>>.
- [RFC4360] Sangli, S., Tappan, D., and Y. Rekhter, "BGP Extended Communities Attribute", RFC 4360, DOI 10.17487/RFC4360, February 2006, <<https://www.rfc-editor.org/info/rfc4360>>.
- [RFC8174] Leiba, B., "Ambiguity of Uppercase vs Lowercase in RFC 2119 Key Words", BCP 14, RFC 8174, DOI 10.17487/RFC8174, May 2017, <<https://www.rfc-editor.org/info/rfc8174>>.
- [RFC8664] Sivabalan, S., Filsfils, C., Tantsura, J., Henderickx, W., and J. Hardwick, "Path Computation Element Communication Protocol (PCEP) Extensions for Segment Routing", RFC 8664, DOI 10.17487/RFC8664, December 2019, <<https://www.rfc-editor.org/info/rfc8664>>.

Authors' Addresses

Ka Zhang
Huawei
Huawei Bld., No.156 Beiqing Rd.
Beijing
100095
China
Email: zhangka@huawei.com

Zhibo Hu
Huawei
Huawei Bld., No.156 Beiqing Rd.
Beijing
100095
China
Email: huzhibo@huawei.com

Jie Dong
Huawei
Huawei Bld., No.156 Beiqing Rd.
Beijing
100095
China
Email: jie.dong@huawei.com