

P802.3cx

Submitter Email: david_law@ieee.org**Type of Project:** Amendment to IEEE Standard 802.3-2018**PAR Request Date:** 12-Sep-2019**PAR Approval Date:****PAR Expiration Date:****Status:** Unapproved PAR, PAR for an Amendment to an existing IEEE Standard

1.1 Project Number: P802.3cx**1.2 Type of Document:** Standard**1.3 Life Cycle:** Full Use

2.1 Title: Standard for EthernetAmendment: Media Access Control (MAC) service interface and management parameters to support improved Precision Time Protocol (PTP) timestamping accuracy

3.1 Working Group: Ethernet Working Group (C/LM/WG802.3)**Contact Information for Working Group Chair****Name:** David Law**Email Address:** david_law@ieee.org**Phone:** +44 1631 563729**Contact Information for Working Group Vice-Chair****Name:** Adam Healey**Email Address:** adam.healey@broadcom.com**Phone:** 6107123508

3.2 Sponsoring Society and Committee: IEEE Computer Society/LAN/MAN Standards Committee (C/LM)**Contact Information for Sponsor Chair****Name:** Paul Nikolich**Email Address:** p.nikolich@ieee.org**Phone:** 8572050050**Contact Information for Standards Representative****Name:** James Gilb**Email Address:** gilb@ieee.org**Phone:** 858-229-4822

4.1 Type of Ballot: Individual**4.2 Expected Date of submission of draft to the IEEE-SA for Initial Sponsor Ballot:** 11/2020**4.3 Projected Completion Date for Submittal to RevCom****Note: Usual minimum time between initial sponsor ballot and submission to Revcom is 6 months.:** 05/2021

5.1 Approximate number of people expected to be actively involved in the development of this project: 20**5.2.a. Scope of the complete standard:** This standard defines Ethernet local area, access and metropolitan area networks. Ethernet is specified at selected speeds of operation; and uses a common media access control (MAC) specification and management information base (MIB). The Carrier Sense Multiple Access with Collision Detection (CSMA/CD) MAC protocol specifies shared medium (half duplex) operation, as well as full duplex operation. Speed specific Media Independent Interfaces (MIIs) provide an architectural and optional implementation interface to selected Physical Layer entities (PHY). The Physical Layer encodes frames for transmission and decodes received frames with the modulation specified for the speed of operation, transmission medium and supported link length. Other specified capabilities include: control and management protocols, and the provision of power over selected twisted pair PHY types.**5.2.b. Scope of the project:** Define optional enhancements to Ethernet support for time synchronization protocols to provide improved timestamp accuracy in support of ITU-T Recommendation G.8273.2 'Class C' and 'Class D' system time error performance requirements.**5.3 Is the completion of this standard dependent upon the completion of another standard:** No**5.4 Purpose:** This document will not include a purpose clause.**5.5 Need for the Project:** Ethernet can be applied in important new applications if implementations can interwork to meet more stringent time synchronization. Potential new applications include use in the 5G radio access network (RAN) infrastructure, high-speed telecommunications,

industrial control and SmartGrid. For example, there is a strong desire to be able to use Ethernet for 5G RAN, which is expected to have significant volume.

5.6 Stakeholders for the Standard: Stakeholders identified to date include but are not limited to: users and producers of systems and components for mobile radio access networks, telecommunications, industrial control, and SmartGrid.

Intellectual Property

6.1.a. Is the Sponsor aware of any copyright permissions needed for this project?: No

6.1.b. Is the Sponsor aware of possible registration activity related to this project?: No

7.1 Are there other standards or projects with a similar scope?: No

7.2 Joint Development

Is it the intent to develop this document jointly with another organization?: No

8.1 Additional Explanatory Notes: Item 5.2B: ITU-T Recommendation G.8273.2 Timing characteristics of telecom boundary clocks and telecom time slave clocks