

P802.1Qcr

Submitter Email: johannes.specht@uni-due.de

Type of Project: Modify Existing Approved PAR

PAR Request Date: 21-May-2018

PAR Approval Date:

PAR Expiration Date:

Status: Unapproved PAR, Modification to a Previously Approved PAR for an Amendment

Root PAR: P802.1Qcr **Approved on:** 30-Jun-2016

1.1 Project Number: P802.1Qcr

1.2 Type of Document: Standard

1.3 Life Cycle: Full Use

2.1 Title: Standard for Local and metropolitan area networks--Bridges and Bridged Networks

Standard for Local and Metropolitan Area Networks-Bridges and Bridged Networks Asynchronous Traffic Shaping

Changes in title: Standard for Local and metropolitan area networks--Bridges and Bridged Networks Standard for Local and Metropolitan Area Networks-Bridges and Bridged Networks Asynchronous Traffic Shaping

3.1 Working Group: Higher Layer LAN Protocols Working Group (C/LM/WG802.1)

Contact Information for Working Group Chair

Name: John Messenger

Email Address: j.l.messenger@ieee.org

Phone: +441904699309

Contact Information for Working Group Vice-Chair

Name: John Messenger

Email Address: j.l.messenger@ieee.org

Phone: +441904699309

3.2 Sponsoring Society and Committee: IEEE Computer Society/LAN/MAN Standards Committee (C/LM)

Contact Information for Sponsor Chair

Name: Paul Nikolich

Email Address: p.nikolich@ieee.org

Phone: 8572050050

Contact Information for Standards Representative

Name: James Gilb

Email Address: gilb@ieee.org

Phone: 858-229-4822

4.1 Type of Ballot: Individual

4.2 Expected Date of submission of draft to the IEEE-SA for Initial Sponsor Ballot: 01/2020

4.3 Projected Completion Date for Submittal to RevCom

Note: Usual minimum time between initial sponsor ballot and submission to Revcom is 6 months.: 10/2020

5.1 Approximate number of people expected to be actively involved in the development of this project:

5.2.a. Scope of the complete standard: This standard specifies Bridges that interconnect individual LANs, each supporting the IEEE 802 MAC

Service using a different or identical media access control method, to provide Bridged Networks and VLANs.

5.2.b. Scope of the project: This project specifies procedures and managed objects for bridges and end stations to perform asynchronous traffic shaping over full-duplex links with constant bit data rates.

Asynchronous traffic shaping can be modeled as an additional layer of shaped egress queues to merge flows into the existing queue structure. The required minimum number of independent queues at an egress port is adjustable and is at least the number of ingress ports of the particular

Changes in scope of the project: This project specifies procedures and managed objects for ~~a bridges bridge~~ and end stations to perform asynchronous traffic shaping over full-duplex links with constant bit data rates. Asynchronous traffic shaping ~~provides~~ can be modeled as an additional layer of shaped egress queues to merge flows into the existing queue structure. The required minimum number of independent queues at an egress port is adjustable and is at least the number of ingress ports of the particular bridge that require merging.

bridge that require merging.

The amendment specifies an information model for the capabilities of asynchronous traffic shaping. It further specifies a YANG data model and a Management Information Base (MIB) module both based on that information model to support configuration and status reporting. It further defines the relationship between the models introduced by this amendment, and the models in the base standard.

Additionally, this amendment provides an informative framework for worst case delay analysis in static networks with static configurations. This amendment also addresses errors and omissions to existing features.

5.3 Is the completion of this standard dependent upon the completion of another standard: No

5.4 Purpose: Bridges, as specified by this standard, allow the compatible interconnection of information technology equipment attached to separate individual LANs.

5.5 Need for the Project: There is well defined traffic that requires zero congestion loss and deterministic latency. Current bridging standards do not provide a sufficiently fine grained asynchronous traffic mechanism to meet these requirements without using network topology information.

This project specifies mechanisms that do not rely on synchronous communication, thereby providing independence from clock synchronization mechanisms and higher link utilization than synchronous mechanisms.

5.6 Stakeholders for the Standard: Developers, providers, and users of networking services and equipment for streaming of time-sensitive data. This includes software developers, networking integrated circuit developers, bridge and network interface controller vendors, and users.

Intellectual Property

6.1.a. Is the Sponsor aware of any copyright permissions needed for this project?: No

6.1.b. Is the Sponsor aware of possible registration activity related to this project?: Yes

If yes please explain: The YANG Data Model will be assigned a Uniform Resource Name (URN) based on the Registration Authority (RA) URN tutorial and IEEE Std 802d. The Simple Network Management Protocol (SNMP) MIB will be assigned an Object Identifier (OID) based on the RA OID tutorial and IEEE Std 802.

7.1 Are there other standards or projects with a similar scope?: No

7.2 Joint Development

Is it the intent to develop this document jointly with another organization?: No

8.1 Additional Explanatory Notes: #5.2b: The core operation of the intended mechanism on the data plane is described in

<http://www.ieee802.org/1/files/public/docs2015/new-tsn-specht-ubs-queues-0521-v0.pdf>.

#6.1b: IEEE Std 802 IEEE Standard for Local and Metropolitan Area Networks: Overview and Architecture IEEE Std 802d IEEE Standard for Local and Metropolitan Area Networks: Overview and Architecture Amendment 1: Allocation of Uniform Resource Name (URN) Values in IEEE 802 Standards RA URN tutorial: <http://standards.ieee.org/develop/regauth/tut/ieeearn.pdf>

RA OID tutorial: <http://standards.ieee.org/develop/regauth/tut/oid.pdf>